



**TELEDYNE**  
**GAS AND FLAME DETECTION**  
Everywhere you look™

**Protégé ZM**  
Single gas monitor



# Protégé ZM

Single gas monitor

## Keeping Your Workforce Safe Just Got Easier.



The Protege ZM Single Gas Monitor is an easy-to-use, zero-maintenance gas detection solution that delivers high performance in a small, ergonomically designed package. This single gas monitor is incredibly reliable, giving industrial workers and first responders the confidence to focus on the task at hand, not on their equipment.

### **Two years of service, hassle free.**

With one-button activation, adjustable alarm settings and an easy-to-read display the Protégé ZM is simple to use. Just turn it on for the first time, and the monitor does the rest. Using the default settings from the factory there is no need to set up or program the monitor. Once activated, the Protégé ZM monitor does not require charging or calibration so these monitors can be deployed in the field 24 hours a day, every day for two years, maintenance and hassle free.

### **Big Performance in a Small Package.**

Because of its small size and strong, stainless steel alligator clip, the Protégé ZM can be conveniently placed where you want it. The monitor is small, lightweight (less than 3 oz.), ergonomically designed and meets IP67 requirements for ingress protection. The unique Protégé ZM profile fits your hand nicely, making the monitor comfortable to hold. It's so lightweight and small you will forget you're wearing it while it protects you.

### **Easy to use, efficient, portable accessories.**

the Protégé ZM monitor is supported by a portfolio of accessories including a four-bay test station and IR Connect programmer. The test station stores data, programs the monitors and supports bumping, calibrating, hibernating and programming of up to four monitors simultaneously. The test station's simple two-button operation and intuitive design means you'll be up and running in no time.

The IR Connect allows programming and hibernating of individual monitors. You can also use the IR Connect to calibrate your monitor and download event logs.

# Protégé ZM

Single gas monitor



## Customizable settings

- Use hibernate mode for up to one year additional operating life
- Custom or factory-programmed alarm set points
- User configurable bump and calibration reminders
- Multiple LCD display options including real-time gas readings, monitor life remaining or both
- Three point alarms (audible, visual and tactile)
- Data-logging capabilities
- Name or assign monitors using a six-character user ID

## Accessories



IR CONNECT MODULE



TEST STATION

# Protégé ZM

Single gas monitor

## Specifications

Product	
<b>Protégé ZM gas monitor</b>	Protégé ZM Single Gas SO <sub>2</sub> Monitor (High Vis Red)
<b>Protégé ZM accessories</b>	Protégé IR Connect with usb cable Protégé IR Connect spare usb cable Protégé ZM alligator clip Protégé ZM calibration cup Regulator 2al/al/6d 0.5Lpm 10-Ft. Clear tubing 10-Ft. Polyethylene tubing
Monitor specifications	
<b>Physical characteristics</b>	
Size	3.7" H x 2.2" W x 1.3" D
Weight	3.2 Oz (92g)
Operation	One-hand operation
Carrying attachments	Stainless steel alligator clip
Case material	Impact-absorbant rubber overmold
Environmental protection	IP 66/67 (third-party certified)
<b>User interface</b>	
Display info	Time remaining (default) or gas reading (optional) or both (optional), gas type, functional test validation, bump test due indicator, battery level
<b>Monitoring</b>	
Sensor types	SO <sub>2</sub>
Hibernation mode supported	Yes
Sensor ranges	0-50ppm
<b>Power</b>	
Power source	Lithium battery
Battery life indication	Yes
Battery life	2 Years, hibernate mode extends life up to one additional year
<b>Alarms</b>	
Visual alarm	Yes - red led
Audible alarm	Yes - 95db
Vibrating alarm	Yes
Alarm set points	Pre-programmed default settings; customized factory settings available; configure use settings via software and the IR Connect or test station accessories
<b>Data storage</b>	
Data logging	Logs last 25 events
Data retention	Yes - backup to PC
Data transmission	Infrared
<b>Certifications</b>	
EMC compliance	CE marked; EMC\EMI\RFI compliant
Explosive atmospheres	QPS ML3448-1 CLASS I DIVISION 1, Groups A, B, C and D IECEX ia IIC T4 Ga; ATEX ia IIC T4 Ga
Approvals	CE mark includes both Atex & EMC testing IP 67 Rated: 3rd-party tested for compliance, EMC: EMC Directive (2004/108/EC) CE Mark
<b>Temperature range</b>	-40°C to 50°C

Teledyne GMI Ltd quality assurance programmes demand the continuous assessment and improvement of all Teledyne GMI Ltd products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact Teledyne GMI Ltd or their representative if you require more details.



**AMERICAS**  
14880 Skinner Rd  
Cypress, TX 77429  
USA  
Tel.: +1 713-559-9200

**EMEA**  
Inchinnan Business Park  
Renfrew, PA4 9RG  
Scotland, UK  
Tel.: +44 (0)141 812 3211

**ASIA PACIFIC**  
Room 04, 9th Floor  
275 Ruijing Road  
Xuhui District, Shanghai, China  
TGFD\_APAC@teledyne.com